CERATO

DATA SHEET

FINISH	Pre-finished with seven coats of WOCA Denmark UV oil.

Cerato solid wooden floors are sought-after for a traditional, stately home look, because they are smoked, deep brushed, chiselled, distressed and hand-scraped.

Dove Grey

Mink Grey

Danish White

Greymist

PRODUCT DETAILS	
Construction	Engineered
Species	Oak
Grade	Rustic
Surface	Hand-chiselled with raised knots
Pattern	Strip pattern 
Profile	Tongue and groove
Edge Profile	Bevelled edge
Top Layer	6mm solid European oak
Backing	Birch and poplar multiply

PLANK SIZES					
	Thickness		Width		Length
	20/6	×	260	×	2200mm

INSTALLATION METHOD	
	Glue Down Elastomeric
	Floated on underlay

TECHNICAL CRITERIA	
Origin	Europe
Formaldehyde	Emission E1
Pentachlorophenol	Emission <5ppm
Slip Testing	65 PTV
European reaction to fire classification	Cfl-s1
Thermal Conductivity	0.17 W/m
Underfloor Heating	Temperature compliant to max 26°C

Cape Town: 021 510 2846 | Paarden Eiland
Johannesburg: 011 262 3117 | Sandton
Durban: 031 000 1000 | Umhlanga
nick@oggie.co.za
www.oggieflooring.com

Oggie hardwood flooring